SECTION 1 MATERIAL NAME / IDENTIFIER

Product Name: Gas Fireplace Glass WHMIS: B3, D2A, D2B

Cleaner Product Code: KK0044

Manufacturer's Name: Imperial Manufacturing Group Inc.

Street Address:
City:

40 Industrial Park Street
Richibucto, NB Canada

Postal Code: E4W 4A4

www.imperialgroup.ca

Emergency Telephone: Canutec (613) 996-6666 (Collect, 24 hours)

Chemical Name:Not applicableChemical Family:Not applicableChemical Formula:Proprietary Blend

Trade Name & Synonyms: Not applicable

Molecular Weight: Not applicable

Material Use: Fireplace Glass Cleaner

SECTION 2 HAZARDS IDENTIFICATION

GHS classification: H227, Flammable Liquids, Category 4

H316, Skin corrosion/irritation, Category 3

H317, Sensitisation, skin Category 1

H336, Specific target organ toxicity, single exposure; Narcotic effects, Category 3

H372, Specific target organ toxicity, repeated exposure, Category 1

Symbol:





Signal Word: Danger

Hazard statements: Combustible liquid. Causes mild skin irritation. Repeated exposure may cause skin

dryness or cracking (EUH066). May cause an allergic skin reaction. May cause drowsiness or dizziness. Causes damage to the lungs through prolonged or

repeated exposure.

Precautionary statements: P260: Do not breathe dust.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P272: Contaminated work clothing should not be allowed out of the workplace.

P285: In case of inadequate ventilation wear respiratory protection.

P302+P352: If on skin, wash with plenty of soap and water.

P304+P340: If inhaled, remove victim to fresh air and keep at rest in a position Comfortable for breathing.

P314: Get medical attention if you feel unwell.

P321: Specific treatment (see...on this label).

P332+P313: If skin irritation occurs, seek medical attention.

P363: Wash contaminated clothing before reuse.

P403+P233: Store in a dry place. Keep container tightly closed.

P405: Store locked up.

P501: Dispose of contents in a fireproof container in accordance with federal, provincial and local regulations.

SECTION 3 COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient	CAS#	% Concentration	
Stoddard Solvent	8052-41-3	10 - 30	
Morpholine	110-91-8	1 - 5	
Monoisopropanolamine	78-96-6	1 - 5	
Isopropyl Alcohol	67-63-0	1 – 5	
Silica (Diatomaceous Earth)	68855-54-9	7 - 13	

May contain up to 72.5% Crystalline Silica

Cristobalite CAS# 14464-46-1 Quartz CAS# 14808-60-7

SECTION 4 FIRST AID MEASURES

Inhalation: If breathing is difficult, remove to fresh air and seek medical attention.

Skin Contact: Wash thoroughly with soap and water.

Eye Contact: Flush eyes with copious amounts of water for 15 minutes. Seek immediate medical attention.

Ingestion: Drink 2 or 3 glasses of water. Do not induce vomiting. Contact a physician.

Note to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs, producing

chemical pneumonitis. Cardiac arrhythmias have been reported with solvent exposure. If more than 2 ml/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of

-:----lass Olass Olassas

gag reflex, convulsions or unconsciousness occur before vomiting. Gastric lavage with a cuffed endotracheal tube should be considered. This product contains material that may cause severe pneumonitis if aspirated. If ingestion has occurred less than 2 hours earlier, carry out careful gastric lavage using endotracheal cuff to prevent aspiration. Observe patient for respiratory difficulty for aspiration pneumonitis. Administer artificial resuscitation and appropriate chemotherapy if respiration is depressed.

SECTION 5 FIRE – FIGHTING MEASURES

Hazardous Combustion Products: CO, CO2 and oxides of nitrogen

Unusual Fire or Explosion Hazards: Source of ignition

Sensitivity to Mechanical Impact: None

Rate of Burning: Not available Explosive Power: Not available

Sensitivity to Static Discharge: Yes, if solvent vapours are present.

Fire Extinguishing Media: Water spray, CO2, and dry chemical

Instructions to the Fire Fighters: See below.

Fire Fighting Protective Equipment: Wear a self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Leak And Spill Procedure: Remove all sources of ignition. Absorb with synthetic or natural absorbent and

dispose in a fireproof container.

SECTION 7 HANDLING AND STORAGE

HANDLING

Handling Practices: Eliminate all sources of ignition. Wear gloves and safety glasses when handling.

Keep containers closed when not in use.

Ventilation Requirements: Use in a well ventilated area.

STORAGE

Ventilation Requirements: None

Storage Requirements: Store in a cool, dry area. Keep away from open flames and other sources of

Ignition. Do not freeze.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Engineering Controls: Use in a well ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Skin (Specify): Nitrile or rubber gloves, if skin contact is likely.

Eye (Specify): Safety glasses or goggles, if eye contact is likely.

Respiratory (Specify): Wear organic vapour mask if prolonged use in a non-ventilated area is unavoidable.

Other (Specify): If long-term inhalation of product dusts are encountered wear an approved dust cartridge

on the air-purifying respirator. Eye wash and shower stations are close to work area.

SECTION 9 PHYSICAL DATA FOR MATERIAL

Physical State: Gas Liquid X Paste

Odour & Appearance: Opaque beige viscous liquid.

Odour Threshold (ppm): Not available

Flammability: Yes \underline{X} No

If Yes, Under Which Conditions?: Source of ignition.

Auto Ignition Temperature (Celsius): Not available

Upper Explosion Limit (% By Volume): 5.0 (Stoddard Solvent)

Lower Explosion Limit (% By Volume): 1.0 (Stoddard Solvent)

Decomposition Temp (°C) Not available

Specific Gravity:1.001 – 10.020 g/mlViscosity:3500 – 7500 cpsVapour Pressure (mm):Not available

Vapour Density (Air-1):

Flashpoint (°C)

Evaporation Rate

Boiling Point (°C):

Not available

Not available

Not available

Below 0°C

Solubility In Water (20°C): partially dispersible

% Volatile (By Weight) 79%

PH: 10.0 – 11.5

Coefficient Of Water/Oil Distribution: Not available

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: Yes X No

If No, Under Which Conditions?:

Incompatibility To Other Substances: Yes X No

If So, Which Ones: Strong oxidizers.

Conditions to Avoid:None under normal conditions.

Hazardous Decomposition Products: Burning may produce hydrocarbon smoke, CO, CO2 and oxides of

nitrogen.

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS

Inhalation: Exposure to high vapour concentration can cause headache, dizziness and vomiting.

The liquid when aspirated into the lungs, can cause severe inflammation of the lungs.

Skin Contact: Mild irritant.

Eye Contact: Vapours are mildly irritating to the eyes.

Ingestion: Burning sensation of the mouth and throat.

CHRONIC HEALTH EFFECTS: May cause defatting and drying of the skin. Prolonged skin contact may cause dermatitis.

Prolonged inhalation of vapours may cause Central Nervous System depression. This product contains micro crystalline silica which is a known carcinogen. Long-term

Inhalation of product dusts may cause silicosis.

Other Health Effects: Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this

product.

LD 50 of Material (Specify Species and Routes): Stoddard Solvent: 5g/kg, Oral (Rat), >3g/kg, Dermal (Rabbit)

Morpholine: 1050mg/kg, Oral (Rat), 310mg/kg, Dermal (Rabbit)

Monoisopropanolamine: 1715mg/kg, Oral (Rat)

Isopropyl Alcohol: 5045mg/kg, Oral (Rat), 6.29g/kg, Dermal (Rabbit)

Silica: Not available

LC 50 of Material (Specify Species and Routes): Stoddard Solvent: >5500mg/m3, 4hr, Inhalation (Rat)

Morpholine: Not available

Monoisopropanolamine: Not available

Isopropyl Alcohol: 16970ppm, 4hr, Inhalation (Rat)

Silica: Not available.

Exposure (Limits): Stoddard Solvent: ACGIH: 100ppm TLV-TWA, OSHA: 100ppm TWA, 525mg/m3 TWA.

Morpholine: ACGIH: 20ppm TLV-TWA, OSHA: 20ppm TWA, 70mg/m3 TWA.

Monoisopropanolamine: Not available

Isopropyl Alcohol: ACGIH: 200ppm TWA, OSHA: 400ppm TWA, 980mg/m3 TWA.

Silica: Cristobalite; ACGIH: TWA – 0.025mg/m3, respirable

Quartz; ACGIH: TWA - 0.025mg/m3, respirable

Irritancy of Material: Mild skin and eye irritant.

Sensitization of Material: May cause skin sensitization or other allergic responses.

Synergistic Materials: None known

Carcinogenicity, Mutagenicity, Reproductive Effects, Teratogenicity: This product is not a mutagen, teratogen or

have other reproductive effects. The product does contain micro crystalline silica which is a known carcinogen by inhalation. Therefore, avoid long-term inhalation of dried product

residues.

SECTION 12

ECOLOGICAL INFORMATION

Ecotoxicity Not available.

Environmental Fate

Biodegradability: Not available.

Bioaccumulative Potential: Not available.

Mobility In Soil: Not available.

SECTION 13

DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose absorbed material in a fireproof container in accordance with federal, provincial

and local regulations.

Safe Handling of Residues: Wash residues with warm soapy water.

Disposal of Packaging: Dispose of containers in accordance with federal, provincial and local regulations.

SECTION 14

TRANSPORTATION INFORMATION

CANADIAN TDG ACT SHIPPING DESCRIPTION: Limited Quantity

Proper shipping name: Not applicable
Class: Not applicable
Packing group: Not applicable

UN: Not applicable

US DOT CLASSIFICATION (49CFR 172.101, 172.102): Limited Quantity

Proper shipping name: Not applicable
Class: Not applicable
Packing group: Not applicable
UN: Not applicable

SECTION 15

REGULATORY INFORMATION

CANADA All components are listed on the DSL or exempt.

WHMIS: B3, D2A, D2B

USA All components are listed on the TSCA or exempt.

INTERNATIONAL Not available

SECTION 16

OTHER INFORMATION

Prepared By (Group, Department, Etc.): Imperial Manufacturing Group Inc. Telephone: (905) 829-5888

Preparation Date: January 1, 1996
Date Revised: March 2, 2020

Additional Notes Or References:

While Imperial Manufacturing Group Inc. believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data are not to be taken as a warranty or representation for which Imperial Manufacturing Group Inc. assumes legal responsibility. They are offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, Provincial/State and local laws and regulations.