

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name	Gasket Adhesive
Product Code(s):	KK0149, KKW1041
Alternative names	Sodium silicate solution (1.6<MR<=2.6)
CAS No.	1344-09-8
EINECS No.	215-687-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s)	Stove gasket adhesive
Uses advised against	None known.

1.3 Details of the supplier of the safety data sheet

Company Identification	Imperial Manufacturing Group Inc. 40 Industrial Park Street Richibucto, NB Canada E4W 4A4 www.imperialgroup.ca
Telephone:	905-829-5888

1.4 Emergency telephone number

Emergency Phone No.	(24 hours) Canutec (613) 996-6666 (Collect)
---------------------	---

SECTION 2: HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification	Skin Irrit. 2 Eye Dam. 1
---------------------------	-----------------------------

Hazards summary

Alkaline.
Risk of serious damage to eyes.
Irritating to skin.

2.2 Label elements



Hazard pictogram(s)
Signal word(s)

Danger

Hazard statement(s)

H315: Causes skin irritation.
H318: Causes serious eye damage.

Precautionary statement(s)

P262: Do not get in eyes, on skin, or on clothing.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards

Dries to form glass film, which can easily cut skin. Spilled material is very slippery. Can etch glass if not promptly removed.

SECTION3:COMPOSITION/INFORMATIONONINGREDIENTS

Regulation (EC) No. 1272/2008 (CLP)

Ingredient(s)	%W/W	CAS No.	EINECS No. / REACH Registration	Hazard symbol(s) and hazard statement(s)
Silicic acid, sodium salt (1.6<MR<=2.6)	47.1	1344-09-8	215-687-4 01-2119448725-31	H315 : Skin Irrit. 2 ; H318 : Eye Dam. 1 ; H335 : STOT SE 3 ;
Water	52.9	7732-18-5	231-791-2	

SECTION4:FIRSTAIDMEASURES

4.1 Description of first aid measures

Eye Contact

Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 15 minutes. Obtain immediate medical attention.

Skin Contact

Wash affected skin with plenty of water. If symptoms develop, obtain medical attention.

Inhalation

Remove patient from exposure, keep warm and at rest. Obtain medical attention.

Ingestion

Do not induce vomiting. Wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Alkaline.
 Risk of serious damage to eyes.
 Irritating to skin.
 The toxicity of sodium silicate is dependent on the silica to alkali ratio and on the pH.
 Obtain immediate medical attention.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION5:FIRE-FIGHTINGMEASURES

5.1 Extinguishing media

Suitable Extinguishing Media

Compatible with all standard fire fighting techniques.

Unsuitable extinguishing Media

None known.

5.2 Special hazards arising from the substance or mixture

Not applicable. Aqueous solution. Non-combustible.

5.3 Advice for fire-fighters

None.

SECTION6:ACCIDENTALRELEASEMEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Wear suitable protective clothing. Wear eye/face protection. See Section: 8.2
6.2 Environmental precautions	Do not allow to enter drains, sewers or watercourses. Advise Authorities if spillage has entered water course or sewer or has contaminated soil or vegetation.
6.3 Methods and materials for containment and cleaning up	Caution - spillages may be slippery. Contain spillages with sand, earth or any suitable adsorbent material. Transfer to a container for disposal or recovery.
6.4 Reference to other sections	See Also Section 8.

SECTION7:HANDLINGANDSTORAGE

7.1 Precautions for safe handling	Avoid contact with eyes, skin and clothing. Avoid generation of mist. Provide adequate ventilation. Emergency shower and eye wash facilities should be readily available. See Also Section 8
7.2 Conditions for safe storage, including any incompatibilities	Storage temperature 0-95° C. Loading temperature 45-95 ° C. Do not allow material to freeze. Provide an adequate bund wall. Unsuitable containers: Aluminium See Also Section 10.

SECTION8:EXPOSURECONTROLS/PERSONALPROTECTION

8.1 Control parameters

SUBSTANCE.	Occupational Exposure Limits
Silicic acid, sodium salt	No Occupational Exposure Limit assigned. An exposure limit of 2 mg/m3 (15 min TWA) is recommended by analogy with sodium hydroxide (UK EH40).

8.2 Exposure controls	Wear protective equipment to comply with good occupational hygiene practice. Do not eat, drink or smoke at the work place.
8.2.1 Appropriate engineering controls	Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions.
8.2.2 Personal Protection	Respiratory protection not normally required. Advice on respiratory protective equipment is given in the HSE (Health and Safety Executive) publication HS(G)53.
Respiratory protection	Chemical goggles (EN 166).
Eye/face protection	Wear suitable protective clothing and gloves.
Skin protection	Plastic or rubber gloves. For example EN374-3, level 6 breakthrough time (>480min).
	Wear suitable overalls. For example EN ISO 13982 (dust), EN 14605 (liquid splashes).
8.2.3 Environmental Exposure Controls	The primary hazard of sodium silicate is the alkalinity. Avoid release to the environment.

SECTION9:PHYSICALANDCHEMICALPROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Liquid . Almost colourless. White or translucent.
Odour	Odourless. (musty)
Odour Threshold (ppm)	Not applicable.
pH (Value)	Strongly alkaline. 11-13

Freezing Point (°C)	Not applicable.
Melting Point (°C)	Not applicable.
Boiling Point (°C)	100
Flash Point (°C) [Closed cup]	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Explosive Limit Ranges	Not applicable.
Vapour Pressure (mm Hg)	Not applicable.
Vapour Density (Air=1)	No data.
Density (g/ml)	No data.
Solubility (Water)	Soluble.
Solubility (Other)	No data.
Partition Coefficient	No data.
Auto Ignition Point (°C)	Not applicable.
Decomposition Temperature (°C)	Not applicable.
Viscosity (mPa. s)	Not applicable.
Explosive properties	Not applicable.
Oxidising Properties	Not applicable.
9.2 Other information	No data.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	See Section: 10.3
10.2 Chemical stability	Stable.
10.3 Possibility of hazardous reactions	When arc welding vessels containing aqueous solutions of this material, take care to control any explosion risk from hydrogen evolved by electrolysis. Aqueous solutions will react with aluminium, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in contact with acids. Can react with sugar residues to form carbon monoxide.
10.4 Conditions to avoid	See Section: 10.3
10.5 Incompatible materials	See Section: 10.3
10.6 Hazardous decomposition product(s)	None known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	
Ingestion	All symptoms of acute toxicity are due to high alkalinity. Material will cause irritation. Oral LD50 (rat) 3400 mg/kg bw
Inhalation	Mist is irritant to the respiratory tract. All symptoms of acute toxicity are due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m ³
Skin Contact	Material will cause irritation. Dermal LD50 (rat) >5000 mg/kg bw
Eye Contact	Material will cause severe irritation. Risk of serious damage to eyes.
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritation	Irritating to eyes. Risk of serious damage to eyes.
Sensitisation	Not sensitising.
Mutagenicity	No evidence of genotoxicity. In vitro/in vivo negative.
Carcinogenicity	No structural alerts. IARC, NTP, OSHA, ACGIH do not list this product as known or suspected carcinogen.
Reproductive toxicity	No evidence of reproductive toxicity or developmental toxicity.
STOT - single exposure	Not classified
STOT - repeated exposure	Not classified. NOAEL oral (rat) >159 mg/kg bw/d
Aspiration hazard	Not classified
Other information	

SECTION12:ECOLOGICALINFORMATION

12.1 Toxicity	Fish (Brachydanio rerio) LC50 (96 hour) 1108 mg/l Aquatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700 mg/l
12.2 Persistence and degradability	Inorganic. Soluble silicates, upon dilution, rapidly depolymerise into molecular species indistinguishable from natural dissolved silica.
12.3 Bioaccumulative potential	Inorganic. The substance has no potential for bioaccumulation.
12.4 Mobility in soil	Not applicable.
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Other adverse effects	The alkalinity of this material will have a local effect on ecosystems sensitive to changes in pH.

SECTION13:DISPOSALCONSIDERATIONS

13.1 Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Waste material is classified as a RCRA Hazardous waste if it exhibits the corrosive characteristic (pH greater than or equal to 12.5) Dispose of this material and its container to hazardous or special waste collection point. Discharge of this product to sewage treatment works is dependent on local regulations with regard to pH controls.
-------------------------------------	---

SECTION14:TRANSPORTINFORMATION

14.1 UN number	Not applicable.
14.2 Proper Shipping Name	Not applicable.
14.3 Transport hazard class(es)	Not applicable.
14.4 Packing group	Not applicable.
14.5 Environmental hazards	Not classified as a Marine Pollutant.
14.6 Special precautions for user	Unsuitable containers: Aluminium
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

TSCA Inventory Status: Reported/Included.

AICS Inventory Status: Reported/Included.

DSL/NDSL Inventory Status: Reported/Included.

SARA TITLE III: This material is not a listed Toxic Chemical subject to the reporting requirements of SARA Title III §313 and 40 C.F.R. Part 372. Hazard

Categories under SARA Title III §§311/312: Acute.

German Water Hazard Classification VwVwS: Product ID number 1314, WGK class 1 (low hazard to water).

2,0,0

SECTION 16: OTHER INFORMATION

This SDS was last reviewed: 02/2015

The following sections contain revisions or new statements: None.

GHS Classification

Skin Irrit. 2

Eye Dam. 1

Signal word(s)

Danger



Hazard pictogram(s)

Hazard statement(s)

H315: Causes skin irritation.

H318: Causes serious eye damage.

Precautionary statement(s)

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

GLOSSARY

H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

STOT SE 3 : Specific target organ toxicity — single exposure Category 3

R41: Risk of serious damage to eyes.

R38: Irritating to skin.

R37/38: Irritating to respiratory system and skin.

DNEL : Derived No Effect Level

PNEC : Predicted No Effect Concentration

PBT: Persistent, Bioaccumulative and Toxic

EC Classification : According to Directive 67/548/EEC & Directive 1999/45/EC

Notice to the Reader: The information is provided in good faith and is correct to the best of Imperial Manufacturing Group Inc.'s knowledge as of the date hereof and is designed to assist our customers; however Imperial Manufacturing Group Inc. makes no representation as to its completeness or accuracy. Final determination of suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Imperial Manufacturing Group Inc. disclaims all expressed or implied warranties or representations.